



(43) International Publication Date
20 January 2005 (20.01.2005)

PCT

(10) International Publication Number
WO 2005/006385 A2

(51) International Patent Classification: H01J 37/317

(21) International Application Number:
PCT/EP2004/005288

(22) International Filing Date: 17 May 2004 (17.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03016005.5 14 July 2003 (14.07.2003) EP

(71) Applicant (for all designated States except US): ICT IN-
TEGRATED CIRCUIT TESTING GESELLSCHAFT
FÜR HALBLEITERPRÜFTECHNIK MBH [DE/DE];
Ammerthalstrasse 20a, 85551 Heimstetten (DE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): FEUERBAUM,
Hans-Peter [DE/DE]; Arno-Assmann-Strasse 14, 81739
Munich (DE). FROSIEN, Juergen [DE/DE]; Kufstein-
erstrasse 16a, 85521 Riemerling (DE). HOFFMANN,

Ull [DE/DE]; Forststrasse 39a, 85521 Riemerling (DE).
WINKLER, Dieter [DE/DE]; Stademannstrasse 6, 81737
Munich (DE). ADAMEC, Pavel [CZ/DE]; Jagdfeldring
25, 85540 Haar (DE).


(74) Agents: GINZEL, Christian et al.; Zimmermann & Part-
ner, P.O. Box 330 920, 80069 Munich (DE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AB, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: IMAGING SYSTEM WITH MULTI-SOURCE ARRAY



(57) Abstract: The present invention provides a charged particle beam device. The device comprises an emitter array (22) for emitting a plurality of charged particle beams (8). The plurality of charged particle beams are imaged with a lens (12). An electrode unit (14) is provided for accelerating the plurality of charged particle beams. The potential differences between a first potential of the emitter array, a second potential of the electrode unit, and a third potential of a specimen, are controlled by a first control unit (11) and a second control unit. Thereby, the second potential is capable of accelerating the plurality of charged particle beams with respect to the first potential, and the third potential is capable of decelerating the plurality of charged particle beams with respect to the second potential.

BEST AVAILABLE COPY

WO 2005/006385 A2